
Mr.Magoo_P

Pendant Luminaires | 220-240 V 156 topLED 26 W DC - 30 W AC | CRI 90 **8137**



Technical data	
Construction year	2018
Туре	Surface
Installation position	Ceiling
Installation environment	Indoor
Light Source	LED
Circuit structure	topLED
Optics	Diffused
Light emission direction	downward and upward
Nominal power	26 W DC
Total Power	30 W
Source lumens	3077 lm
Voltage	220 - 240 V AC
Frequency	60 - 50 Hz
CCT / Tone	3000 K
Colour rendering index	90 Ra
C.C. / C.V.	AC
Safety class	1
IP	IP20
Optical compartment IP	IP40
Glow wire test	650°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	Driver
Dimmable article	Phase cut
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	Yes
Cable length	2.5 m
Resin potting	No
Type of light emission	Double emission
Net weight	3.950 Kg
Electrostatic discharge protection	No
Surge protection	No

ERE CE 🔬 🕱 🗘 🖻 🛓 C.C. 🥅 1920 🗋 🔶



Finishing casin	g	
Material	Aluminium	
Colour	White	
Processing	Coating	
Finishing diffus	er	

Material	PE
Colour	neutral

Pendant Luminaires | 220-240 V | 156 topLED 26 W DC - 30 W AC | CRI 90 | Base 8137

Double emission pendant luminaires for indoor application. The warm white LED light source with a diffused light distribution is composed of 156 topled LEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 3077 lm, with a 118.3 lm/W nominal luminous efficacy.

The device body is made of aluminium and features a white finish, processed by means of coating; the diffuser is made of pe. The ingress protection degree is IP20; the total weight is of 3.950 kg.

The total absorbed power is 30 W. The power supply cable is included and features a 2.5 m length.

The device features protection class I and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Energy efficiency class

This product contains a light source of energy efficiency class F.

Illuminotechnical Features	
Light Output Ratio (LOR)	68 %
Source lumens	3077 lm
Delivered lumens	2117 lm
Consumption	30 W
Luminaire efficacy	70 lm/W
Colour temperature	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	90 Ra
Junction temperature (lighting fixture)	80
Standard Operating Ambient Temperature	25°C


LED Life / Failure Ratio


L80 B20 C0 80000h

13.4
13.1
S=0.25H
70/50/20

OPTICAL

C0/C180 optics	118°
Light distribution simmetry	Symmetrical





C0/C180 (Half-peak divergence: 117.8°) C90/C270 (Half-peak divergence: 121.0°)

Mr.Magoo_P

Mr.Magoo_P | Pendant Luminaires | Accessories 8137

