Moonflower




Wall Lights | 1 x powerLEDs 0.9 W DC 24 V Modular | RGB

7760





EAC	DMX 512	C€	RoHS	$\overline{\mathbb{X}}$	Ů	C.V.	\bowtie	IP20		<u>•</u>



Finishing casin	
Material	ABS
Colour	White RAL 9003
Processing	Coating

Finishing diffus	er	
Material	PC	
Colour	white	
Processing	Sandblasting	

Electronics



Kit0019

None On/Off Driver 220~240V AC / 176~264V DC $\,$ 19.2 W (- art.)



Kit0020

None On/Off Driver 220~240V AC / 176~264V DC $\,$ 70 W (- art.)



⟨it∩∩21

None On/Off Driver 220~240V AC / 176~264V DC $\,$ 150 W (- art.)



Kit0011

DMX Multi Channel 6ch. 24V DC 288 W (- art.)

Technical data	
Designer	Colin Johnson
Construction year	2014
Туре	Wall Lights
Installation position	Wall lights
Installation environment	Indoor
Light Source	LED
Circuit structure	powerLEDs
Optics	Diffused
Nominal power	0.9 W DC
Voltage	24V
CCT / Tone	RGB
C.C. / C.V.	CV
Safety class	3
IP	IP20
Glow wire test	650°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	No
Dimmable article	DMX
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No
Type of light emission	Single emission
Net weight	0.75 Kg
Modularity	Modular
Electrostatic discharge protection	No
Surge protection	No

Moonflower



Wall Lights | 1 x powerLEDs 0.9 W DC 24 V | Modular | RGB 7760

Single emission wall lights for indoor application. The RGB LED light source with a diffused light distribution is composed of 1 powerled LEDs.

The device body is made of ABS and features a white ral 9003 finish, processed by means of coating; the diffuser is made of PC with a sandblasting treatment. The ingress protection degree is IP20; the total weight is of 0.75 kg. The power supply driver is not provided and is to be ordered separately.

The total absorbed power is 0.9 W.

The device features protection class III and can be wall lights-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Illuminotechnical Features		
Junction temperature (lighting fixture)	85	
Standard Operating Ambient Temperature	25°C	

Moonflower



Moonflower | Wall Lights | Accessories **7760**

		Cable and connector Length 1200 mm; section 0,25 mm²; colors: white - black - yellow.		Code KIT0053
		Cable and connector Length 400 mm; section 0,25 mm²; colors: blue - brown.		Code KIT0054
		Cable and connector Length 600 mm; section 0,35 mm²; colors: black - red.		Code KIT0049
		Cable and connector Section 1 mm ² ; colors: black - red.		Code KIT0052
		Cable and connector Length 320 mm; colors: grey.		Code KIT0050
A. II.		Connector		Code KIT0051
		Bracket Material:ABS, colour:White RAL 9003, processing:Coating.	Finish White	Code KIT0048
	250	Diffuser	Code 7761 _.	Diffusore

5.09.2023