


Xilema_W2



Wall Lights | 220-240 V
60 topLED 30 W DC - 34 W AC | CRI 90
7768



Technical data	
Construction year	2014
Type	Surface
Installation position	Wall lights - Ceiling
Installation environment	Indoor
Light Source	LED
Circuit structure	topLED
Optics	Double Asymmetric
Light emission direction	backward
Nominal power	30 W DC
Total Power	34 W
Source lumens	3407 lm
Voltage	220 - 240 V AC
Frequency	50 - 60 Hz
CCT / Tone	3000 K
Colour rendering index	90 Ra
C.C. / C.V.	AC
Safety class	1
IP	IP20
Optical compartment IP	IP40
Glow wire test	650°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	Driver
Dimmable article	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No
Type of light emission	Single emission
Net weight	2.175 Kg
Electrostatic discharge protection	No
Surge protection	No

Finishing casing	
Material	Aluminium
Colour	translucent

Finishing diffuser	
Material	PMMA
Processing	Sandblasting



Wall Lights | 220-240 V | 60 topLED 30 W DC - 34 W AC | CRI 90 | Base 7768

Single emission wall lights for indoor application. The warm white LED light source with a double asymmetric light distribution is composed of 60 topped LEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 3407 lm, with a 113.6 lm/W nominal luminous efficacy.

The device body is made of aluminium and features a translucent finish; the diffuser is made of pmma with a sandblasting treatment. The ingress protection degree is IP20; the total weight is of 2.175 kg.

The total absorbed power is 34 W.

The device features protection class I and can be wall lights or ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Energy efficiency class

This product contains 4 light sources of energy efficiency class E.

Illuminotechnical Features

Light Output Ratio (LOR)	56 %
Source lumens	3407 lm
Delivered lumens	1914 lm
Consumption	34 W
Luminaire efficacy	56 lm/W
Colour temperature	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	90 Ra
Junction temperature (lighting fixture)	80

Standard Operating Ambient Temperature 25°C

LED Life / Failure Ratio


L80 B20 C0 80000h

UGR

UGR axial	29
UGR transversal	29.1
X=4H Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL

C90/C270 optics	144°
C0/C180 optics	154°
Light distribution symmetry	Symmetrical 2 axis



Distance [m]	Cone diameter [m]	illuminance [lx]
0.5	3.11 4.40	E(0°) 1205 E(C90) 26 E(C0) 7
1.0	6.23 8.80	E(0°) 301 E(C90) 7 E(C0) 2
1.5	9.34 13.20	E(0°) 134 E(C90) 3 E(C0) 1
2.0	12.46 17.61	E(0°) 75 E(C90) 2 E(C0) 0
2.5	15.57 22.01	E(0°) 48 E(C90) 1 E(C0) 0
3.0	18.69 26.41	E(0°) 33 E(C90) 1 E(C0) 0

— C0/C180 (Half-peak divergence: 154.4°)
— C90/C270 (Half-peak divergence: 144.4°)