




Table Lamps | 220-240 V  
1 x powerLED 8.5 W DC - 10 W AC | CRI 90  
**9288**



Technical data	
Construction year	2021
Type	Table Lamps
Installation position	Floor
Installation environment	Indoor
Light Source	LED
Optics	Flood
Light emission direction	frontal
Power	8.5 W
Source lumens	620 lm
Frequency	50 - 60 Hz
CCT / Tone	3000 K
Colour rendering index	90 Ra
C.C. / C.V.	AC
Safety class	2
IP	IP20
Glow wire test	650°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	Driver
Dimmable article	PUSH DIM
Directional	Swivelling
total angle (vertical plane)	360 °
total angle (horizontal plane)	180 °
Tilting	No
Walk-over	No
Drive-over	No
Cable included	Yes
Cable length	2 m
Electric socket	Type C
Resin potting	No
Type of light emission	Single emission
Electrostatic discharge protection	No
Surge protection	No

### Finishing casing

Material	Iron
Processing	Coating

### Finishing diffuser

Material	PMMA
Colour	transparent

### Finishing base

Material	Iron
Processing	Coating



Table Lamps | 220-240 V | 1 x powerLED 8.5 W DC - 10 W AC | CRI 90 | Base 9288

Single emission table lamps for indoor application. The warm white LED light source with a flood light distribution is composed of 1 powered LEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 620 lm, with a 72.9 lm/W nominal luminous efficacy.

The device body is made of iron, processed by means of coating; the diffuser is made of pmma. The ingress protection degree is IP20;

The total absorbed power is 8.5 W. The power supply cable is included and features a 2 m lenght.

The device features protection class II and can be floor-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Illuminotechnical Features	
Light Output Ratio (LOR)	83 %
Source lumens	620 lm
Delivered lumens	518 lm
Consumption	10 W
Luminaire efficacy	51 lm/W
Colour temperature	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	90 Ra
Junction temperature (lighting fixture)	80
Standard Operating Ambient Temperature	25

LED Life / Failure Ratio	
L80 B20 C0 80000h (at Tj 85 Ta 25)	

UGR	
UGR transversal	17.2
UGR axial	17.4
X=4H   Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL	
Light distribution simmetry	Symmetrical
C0/C180 optics	44°

