

Pendant Luminaires | 220-240 V 2 topLED 33 W DC - 36 W AC | CRI 90








Technical data	
Construction year	2021
Туре	Pendant Luminaires
Installation position	Ceiling
Installation environment	Indoor
Light Source	LED
Circuit structure	topLED
Optics	Diffused
Light emission direction	downward and upward
Nominal power	33 W DC
Total Power	36 W
Source lumens	3672 lm
Voltage	220 - 240 V AC
Frequency	50 - 60 Hz
CCT / Tone	2700 K
Colour rendering index	90 Ra
C.C. / C.V.	AC
Safety class	1
IP	IP20
Glow wire test	650°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	Driver
Dimmable article	DALI-2 - PUSH DIM
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	Yes
Cable length	9.3 m
Resin potting	No
Type of light emission	Double emission
Net weight	7.000 Kg
Electrostatic discharge protection	No
Surge protection	No





Finishing casing		
Material	metal - metal	
Colour	White RAL 9003 Matt	
Processing	Coating - Coating	

Finishing diffuser		
Material	PMMA	
Colour	opaline	
Processing	Satin finishing	

Finishing mounting frame		
Material	metal	
Colour	black	
Processing	Coating	

Saliscendi



Pendant Luminaires | 220-240 V | 2 topLED 33 W DC - 36 W AC | CRI 90 | Base **9310**


Double emission pendant luminaires for indoor application. The super warm LED light source with a diffused light distribution is composed of 2 topled LEDs with CCT of 2700 K and a CRI 90; the source luminous flux is 3672 lm, with a 111.3 lm/W nominal luminous efficacy.


The device body is made of metal, processed by means of coating The device body is made of metal and features a white ral 9003 matt finish, processed by means of coating; the diffuser is made of pmma with a satin finishing treatment; the mounting frame is made of metal, with a black finish, processed by means of coating. The ingress protection degree is IP20; the total weight is of 7.000 kg.

The total absorbed power is 36 W. The power supply cable is included and features a 9.3 m length.

The device features protection class I and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.





Energy efficiency class

This product contains 2 light sources of energy efficiency class F.

Illuminotechnical Features	
Light Output Ratio (LOR)	38 %
Source lumens	3672 lm
Delivered lumens	1428 lm
Consumption	36 W
Luminaire efficacy	39 lm/W
Colour temperature	2700 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	90 Ra
Junction temperature (lighting fixture)	80
Standard Operating Ambient Temperature	25°C

LED Life / Failure Ratio

L70 B20 C0 72500h

UGR	
UGR axial	22
UGR transversal	22
X=4H Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL	
C0/C180 optics	64°
Light distribution simmetry	Symmetrical