2Nights_P3

Colgantes | 220-240 V | 3 topLED 7 W DC - 7 W AC
CRI 90
8643



Datos técnicos	
Designer	Davide Oppizzi
Año de realización	2018
Tipo	Superficie
Posición de instalación	Techo
Ambiente de instalación	Interiores
Fuente de luz	LED
Poder total	7 W
Flujo luminoso (fuente)	540 lm
Voltage	220 - 240 V AC
Frequency	60 - 50 Hz
CCT / Tone	3000 K
Índice de rendimientos cromático	90 Ra
C.C. / C.V.	AC
Clase de aislamiento	1
IP	IP20
Test del hilo incandescente	850°
Montaje directo sobre superficies normalmente inflamables	Sí
CE	Sí
Driver incluido.	driver
Artículo regulable	Phase cut
Orientabilidad	No
Basculación	No
Practicabilidad	No
Transitabilidad	No
Cable incluido.	Sí
Largo del cable	3 m
Resinado	No
Tipología de emisión luminosa	Una emisión
Peso neto	1.175 Kg
Protección descargas electrostáticas	No
Protección contra sobretensiones	No

Acabado cuerpo	
Material	aluminio
Color	dorado
Elaboración	Galvanostegia

Acabado difusor	
Material	PC
Color	transparente

Acabado montura	
Material	metal
Color	negro RAL 9005
Elaboración	Pintura

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

2Nights_P3

Colgantes | 220-240 V | 3 topLED 7 W DC - 7 W AC | CRI 90
8643

Single emission pendant luminaires for indoor application. The warm white LED light source with a wide flood light distribution is composed of 3 topled LEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 540 lm, with a 77.1 lm/W nominal luminous efficacy.

The device body is made of aluminium and features a gold finish, processed by means of electroplating; the diffuser is made of PC; the mounting frame is made of metal, with a embossed black ral 9005 finish, processed by means of coating. The ingress protection degree is IP20; the total weight is of 1.175 kg.

The total absorbed power is 7 W. The power supply cable is included and features a 3 m length.

The device features protection class I and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.





Clase de eficiencia energética
Este producto contiene 3 fuentes de luz de clase de eficiencia energética G.

Características Luminotécnicas	
Light Output Ratio (LOR)	50 %
Flujo luminoso (fuente)	540 lm
Flujo luminoso de luminaria	270 lm
Consumption	7 W
Rendimiento luminoso de las luminarias	38 lm/W
Temperatura de color	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Índice de rendimientos cromático	90 Ra
Temperatura de unión (luminaria)	80
Temperatura estándar del ambiente de servicio	25°C

LED Life / Failure Ratio
L70 B20 C0 72500h

UGR	
UGR axial	29.4
UGR transversal	29.4
X=4H | Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL	
Óptica C0/C180	69°
Light distribution simmetry	Symmetrical

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

2Nights_P3

2Nights_P3 | Pendant Luminaires | Accessories
8643



Dimmer
220-240V

Code
KIT0026

Dimmer
Radio-frequenza, 85-240V

Code
KIT0080

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.