
Periscopio

Floor Lamp | 220-240 V | 1xG9 9063



Туре	Floor Lamp
Installation position	Floor
Installation environment	Indoor
Lamp cap	1 x G9
Frequency	50-60 Hz
Optics	Diffused
Safety class	2
IP	IP20
Glow wire test	650°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Dimmable article	No
Directional	No
Tilting	Yes
total angle (horizontal plane)	330 °
total angle (vertical plane)	180 °
Walk-over	No
Drive-over	No
Cable included	Yes
Electric socket	Туре С
Cable length	4 m
Resin potting	No
Net weight	8.650 Kg

$[\blacksquare \ \mathsf{c} \mathsf{c} \ \swarrow \ \textcircled{R} \ \r{R} \$



-
]
AISI 304 steel
Red RAL 3020
Coating
er
Glass - Glass
white - grey
Satin finishing - Coating
Iron
Coating

Periscopio

Floor Lamp | 220-240 V | 1xG9 9063

Double emission floor lamp for indoor application. LED lamplamp included, lamp cap 1xG9.

The device body is made of aisi 304 steel and features a red ral 3020 finish, processed by means of coating; the diffuser is made of glass with a satin finishing treatment; the diffuser is made of glass with a coating treatment. The ingress protection degree is IP20; the total weight is of 8.650 kg.

. The power supply cable is included and features a 4 m length.

The device features protection class II and can be floor-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Energy efficiency class

This product contains a light source of energy efficiency class F.

Illuminotechnical Features	
Source lumens	700 lm
Colour temperature	3000 K
Colour rendering index	80 Ra
Junction temperature (lighting fixture)	80
Standard Operating Ambient Temperature	25°C

