


Wall Lights | 220-240 V
12 topLED 4.8 W DC 200 mA | Modular | CRI 80 | Dynamic White
7782



Technical data	
Designer	Colin Johnson
Construction year	2019
Type	Surface
Installation position	Wall lights
Installation environment	Indoor
Light Source	LED
Circuit structure	topLED
Optics	Diffused
Light emission direction	frontal
Nominal power	4.8 W DC
Voltage	220 - 240 V AC
Frequency	60 - 50 Hz
Source lumens 149K	1800 lm
Temperatura colore minima	149 K
Source lumens 248K	5000 lm
Temperatura colore massima	248 K
CCT / Tone	Dynamic White
Colour rendering index	80 Ra
C.C. / C.V.	AC
Safety class	2
IP	IP20
Glow wire test	650°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	Driver
Dimmable article	Yes
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No
Type of light emission	Single emission
Net weight	0.75 Kg
Modularity	Modular
Electrostatic discharge protection	No
Surge protection	No

Finishing casing	
Material	ABS
Colour	White RAL 9003
Processing	Coating

Finishing diffuser	
Material	PC
Colour	white
Processing	Sandblasting

Wall Lights | 220-240 V | 12 topLED 4.8 W DC 200 mA | Modular | CRI 80 | Dynamic White
7782

Single emission wall lights for indoor application. The dynamic white LED light source with a diffused light distribution is composed of 12 topLED LEDs with CCT of 1800-5000 K and a CRI 80.

The device body is made of ABS and features a white ral 9003 finish, processed by means of coating; the diffuser is made of PC with a sandblasting treatment. The ingress protection degree is IP20; the total weight is of 0.75 kg.

The total absorbed power is W.

The device features protection class II and can be wall lights-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Energy efficiency class	
This product contains a light source of energy efficiency class G.	
Illuminotechnical Features	
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	80 Ra
Junction temperature (lighting fixture)	80
Standard Operating Ambient Temperature	25°C
LED Life / Failure Ratio	
L70 B20 C0 136000h	