


Colgantes | 220-240 V
200 topLED 42 W DC - 42 W AC | CRI 90
8619



Datos técnicos	
Año de realización	2018
Tipo	Superficie
Posición de instalación	Techo
Ambiente de instalación	Interiores
Fuente de luz	LED
Poder total	42 W
Flujo luminoso (fuente)	5671 lm
Voltage	220 - 240 V AC
Frequency	60 - 50 Hz
CCT / Tone	3000 K
Índice de rendimientos cromático	90 Ra
C.C. / C.V.	AC
Clase de aislamiento	1
IP	IP40
Test del hilo incandescente	850°
Montaje directo sobre superficies normalmente inflamables	Sí
CE	Sí
Driver incluido.	driver
Artículo regulable	Phase cut
Orientabilidad	No
Basculación	No
Practicabilidad	No
Transitabilidad	No
Cable incluido.	Sí
Largo del cable	2.3 m
Resinado	No
Tipología de emisión luminosa	Dos emisiones
Peso neto	4.9 Kg
Protección descargas electrostáticas	No
Protección contra sobretensiones	No



Acabado cuerpo	
Material	metal
Color	Oro Rosa
Elaboración	Galvanostegia

Acabado difusor	
Material	PC
Color	opalino

Acabado montura	
Material	metal
Color	relieve blanco RAL 9003
Elaboración	Pintura

Colgantes | 220-240 V | 200 topLED 42 W DC - 42 W AC | CRI 90
8619


Double emission pendant luminaires for indoor application. The warm white LED light source with a diffused light distribution is composed of 200 topLED LEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 5671 lm, with a 135.0 lm/W nominal luminous efficacy.

The device body is made of metal and features a rose gold finish, processed by means of electroplating; the diffuser is made of PC; the mounting frame is made of metal, with a embossed white ral 9003 finish, processed by means of coating. The ingress protection degree is IP40; the total weight is of 4.9 kg.

The total absorbed power is 42 W. The power supply cable is included and features a 2.3 m length.

The device features protection class I and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.



0.5	1.87 1.93	E(0°) E(C90) E(C0)	3387 177 168
1.0	3.75 3.86	E(0°) E(C90) E(C0)	847 44 42
1.5	5.62 5.79	E(0°) E(C90) E(C0)	376 20 19
2.0	7.49 7.72	E(0°) E(C90) E(C0)	212 11 10
2.5	9.36 9.65	E(0°) E(C90) E(C0)	135 7 7
3.0	11.24 11.58	E(0°) E(C90) E(C0)	94 5 5

Distance [m] Cone diameter [m] Illuminance [lx]

— C0/C180 (Half-peak divergence: 125.2°)
— C90/C270 (Half-peak divergence: 123.8°)


Clase de eficiencia energética	
Este producto contiene 2 fuentes de luz de clase de eficiencia energética F.	

Características Luminotécnicas	
Light Output Ratio (LOR)	52 %
Flujo luminoso (fuente)	5671 lm
Flujo luminoso de luminaria	3002 lm
Consumption	42 W
Rendimiento luminoso de las luminarias	71 lm/W
Temperatura de color	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Índice de rendimientos cromático	90 Ra
Temperatura de unión (luminaria)	80
Temperatura estándar del ambiente de servicio	25°C

LED Life / Failure Ratio	
L80 B20 C0 80000h	

UGR	
UGR axial	17.2
UGR transversal	17.5
X=4H Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL	
Óptica C0/C180	124°
Light distribution simmetry	Symmetrical



Dimmer
220-240V

Code
KIT0026



Dimmer
Radio-frequenza, 85-240V

Code
KIT0080