Oxygen_W2

Lampe murale | 220-240 V
70 topLED 31 W DC - 36 W AC | CRI 90
8192



Données techniques	
Année de réalisation	2018
Typologie	Surface
Position d'installation	Mur
Environnement d'installation	Intérieur
Source lumineuse	LED
Optique	General Lighting
Light emission direction	downward
Puissance nominale	31 W DC
Pouvoir total	36 W
Flux lumineux (source)	3431 lm
Efficacité nominale	240 - Array AC
Frequency	60 - 50 Hz
Température de couleur / Tone	3000 K
Indice de rendu chromatique	90 Ra
C.C. / V.C.	AC
Classe d'isolation	1
IP	IP20
Essai au fil incandescent	650°
Montage direct sur des surfaces normalement inflammables	Oui
CE	Oui
Driver inclus	Driver
Article à intensité variable	PUSH DIM
Orientable	Non
Basculement	Non
Piétinable	Non
Carrossable	Non
Câble inclus	Oui
Longueur du câble	4.5 m
Revêtement en résine	Non
Type d'émission lumineuse	Double émission
Poids net	7.4 Kg
Protection contre les décharges électrostatiques	Non
Protection contre les surtensions	Non

Finition corps	
Matériau	PU
Couleur	azur

Finition diffuseur	
Matériau	PMMA
Couleur	transparent

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Oxygen_W2

Lampe murale | 220-240 V | 70 topLED 31 W DC - 36 W AC | CRI 90
8192

Double emission wall lights for indoor application. The warm white LED light source with a general lighting light distribution is composed of 70 topled LEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 3431 lm, with a 110.7 lm/W nominal luminous efficacy.

The device body is made of pu and features a light blue finish; the diffuser is made of pmma with a laser engravings treatment. The ingress protection degree is IP20; the total weight is of 7.4 kg.

The total absorbed power is 36 W. The power supply cable is included and features a 4.5 m lenght.

The device features protection class I and can be wall lights-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.





Classe d'efficacité énergétique
Ce produit contient 2 sources lumineuses de classe d'efficacité énergétique F.

Caractéristiques Techniques de l'éclairage	
Light Output Ratio (LOR)	63 %
Flux lumineux (source)	3431 lm
Flux lumineux du luminaire	2165 lm
Consumption	36 W
Efficacité lumineuse du luminaire	60 lm/W
Température de couleur	3000 K
Standards de Concordance de Couleur	3 Step MacAdam
Indice de rendu chromatique	90 Ra
Température de jonction (appareil)	80
Température standard de l'environnement de	25°C

LED Life / Failure Ratio
L80 B20 C0 80000h

UGR	
UGR axial	12.7
UGR transversal	12.7
X=4H | Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL	
Light distribution simmetry	Symmetrical
Optique C0/C180	138°

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.