



Colgantes | 220-240 V
165 topLED 85 W DC - 89 W AC | CRI 90
8522



Datos técnicos	
Designer	Pio e Tito Toso
Año de realización	2016
Tipo	Superficie
Posición de instalación	Techo
Ambiente de instalación	Interiores
Fuente de luz	LED
Circuit structure	topLED
Óptica	Difusa
Light emission direction	downward and upward
Potencia nominal	85 W DC
Poder total	89 W
Flujo luminoso (fuente)	8741 lm
Voltage	220 - 240 V AC
Frequency	60 - 50 Hz
CCT / Tone	3000 K
Índice de rendimientos cromático	90 Ra
C.C. / C.V.	AC
Clase de aislamiento	1
IP	IP20
Test del hilo incandescente	850°
Montaje directo sobre superficies normalmente inflamables	Sí
CE	Sí
Driver incluido.	driver
Artículo regulable	DALI - PUSH DIM
Orientabilidad	No
Basculación	No
Practicabilidad	No
Transitabilidad	No
Cable incluido.	Sí
Largo del cable	5000 m
Resinado	No
Tipología de emisión luminosa	Dos emisiones
Peso neto	6.330 Kg
Protección descargas electrostáticas	No
Protección contra sobretensiones	No

Acabado cuerpo

Material	aluminio
Color	Blanco
Elaboración	Pintura

Acabado difusor

Material	PC
Color	transparente

Acabado montura

Material	metal
Color	Blanco
Elaboración	Pintura

Cables Electrification+suspension

Longitud máxima de	5000 mm
--------------------	---------

Colgantes | 220-240 V | 165 topLED 85 W DC - 89 W AC | CRI 90
8522


Double emission pendant luminaires for indoor application. The warm white LED light source with a diffused light distribution is composed of 165 topLED LEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 8741 lm, with a 102.8 lm/W nominal luminous efficacy.

The device body is made of aluminium and features a white finish, processed by means of coating; the diffuser is made of PC; the mounting frame is made of metal, with a white finish, processed by means of coating. The ingress protection degree is IP20; the total weight is of 6.330 kg.

The total absorbed power is 89 W. The power supply cable is included and features a 5000 m length.

The device features protection class I and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.




Clase de eficiencia energética	
Este producto contiene 6 fuentes de luz de clase de eficiencia energética F.	

Características Luminotécnicas	
Light Output Ratio (LOR)	81 %
Flujo luminoso (fuente)	8741 lm
Flujo luminoso de luminaria	7091 lm
Consumption	89 W
Rendimiento luminoso de las luminarias	79 lm/W
Temperatura de color	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Índice de rendimientos cromático	90 Ra
Temperatura de unión (luminaria)	80
Temperatura estándar del ambiente de servicio	25°C

LED Life / Failure Ratio	
L70 B20 C0 72500h (at Tj 115 Ta 25)	

OPTICAL	
Óptica C90/C270	99°
Óptica C0/C180	139°
Light distribution simmetry	Symmetrical 2 assis

Quad_P9 | Pendant Luminaires | Accessories
8522



Dimmer
Bluetooth, 220-240V

Code
KIT0079