



Pendelleuchte | 220-240 V
165 topLED 49 W DC - 54 W AC | CRI 90
8526



Technische Daten	
Designer	Pio e Tito Toso
Jahr der Verwirklichung	2016
Typ	Oberfläche
Installationsposition	Decke
Installationsumgebung	Indoor
Lichtquelle	LED
Gesamtleistung	54 W
Lichtstrom (Lichtquelle)	5001 lm
Voltage	220 - 240 V AC
Frequency	60 - 50 Hz
Ähnlichste Farbtemperatur / Tone	3000 K
Farbwiedergabeindex	90 Ra
Gleichstrom/Gleichspannung	AC
Isolierklasse	1
IP	IP20
Glühdrahtprüfung	850°
Direkte Montage auf normal entflammaren Oberflächen	Ja
CE	Ja
Einschließlich Driver	Driver
Leuchte dimmbar	Phase cut
Schwenkbarkeit	Nein
Drehbarkeit	Nein
Begehbarkeit	Nein
Überrollbarkeit	Nein
Einschließlich Kabel	Ja
Kabellänge	2000 m
Harzbeschichtung	Nein
Typ Lichtabstrahlung	Zweiflammig
Nettogewicht	6.6 Kg
Schutz vor elektrostatischen Entladungen	Nein
Schutz vor Stoßspannungen	Nein



Oberfläche Gehäuse	
Material	Aluminium
Farbe	Weiß geprägt RAL 9003
Bearbeitungstyp	Lackierung

Oberfläche Diffusor	
Material	PC
Farbe	transparent

Oberfläche Fassung	
Material	Metall
Farbe	Weiß geprägt RAL 9003
Bearbeitungstyp	Lackierung

Pendelleuchte | 220-240 V | 165 topLED 49 W DC - 54 W AC | CRI 90
8526


Double emission pendant luminaires for indoor application. The warm white LED light source with a diffused light distribution is composed of 165 topLEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 5001 lm, with a 102.1 lm/W nominal luminous efficacy.

The device body is made of aluminium and features a embossed white ral 9003 finish, processed by means of coating; the diffuser is made of PC; the mounting frame is made of metal, with a embossed white ral 9003 finish, processed by means of coating. The ingress protection degree is IP20; the total weight is of 6.6 kg.

The total absorbed power is 54 W. The power supply cable is included and features a 2000 m length.

The device features protection class I and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.




Energieeffizienzklasse	
Dieses Produkt enthält 3 Lichtquellen der Energieeffizienzklasse F.	
Illuminotechnical Eigenschaften	
Light Output Ratio (LOR)	92 %
Lichtstrom (Lichtquelle)	5001 lm
Leuchten Lichtstrom	4610 lm
Consumption	54 W
Leuchten Lichtausbeute	85 lm/W
Farbtemperatur	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Farbwiedergabeindex	90 Ra
Verbindungstemperatur (Leuchte)	80
LED Life / Failure Ratio	
L70 B20 C0 72500h (at Tj 115 Ta 25)	
OPTICAL	
Optik C0/C180	110°
Light distribution simmetry	Symmetrical



Quad_P7 | Pendant Luminaires | Accessories

8526



Dimmer
220-240V

Code
KIT0026



Dimmer
Radio-frequenza, 85-240V

Code
KIT0080