Quad_P9

Suspension | 220-240 V
165 topLED 85 W DC - 89 W AC | CRI 90
8523





Données techniques	
Designer	Pio e Tito Toso
Année de réalisation	2016
Typologie	Surface
Position d'installation	Plafond
Environnement d'installation	Intérieur
Source lumineuse	LED
Pouvoir total	89 W
Flux lumineux (source)	8741 lm
Efficacité nominale	240 - Array AC
Frequency	60 - 50 Hz
Température de couleur / Tone	3000 K
Indice de rendu chromatique	90 Ra
C.C. / V.C.	AC
Classe d'isolation	1
IP	IP20
Essai au fil incandescent	850°
Montage direct sur des surfaces normalement inflammables	Oui
CE	Oui
Driver inclus	Driver
Article à intensité variable	DALI - PUSH DIM
Orientable	Non
Basculement	Non
Piétinable	Non
Carrossable	Non
Câble inclus	Oui
Longueur du câble	5000 m
Revêtement en résine	Non
Type d'émission lumineuse	Double émission
Poids net	6.3 Kg
Protection contre les décharges électrostatiques	Non
Protection contre les surtensions	Non

Finition corps	
Matériau	Aluminium
Couleur	noir RAL 9005
Fabrication	Vernissage

Finition diffuseur	
Matériau	PC
Couleur	transparent

Finition monture	
Matériau	métal
Couleur	noir RAL 9005
Fabrication	Vernissage

Cables Electrification+suspension	
Longueur max de	5000 mm

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Quad_P9

Suspension | 220-240 V | 165 topLED 85 W DC - 89 W AC | CRI 90
8523

Double emission pendant luminaires for indoor application. The warm white LED light source with a general lighting light distribution is composed of 165 topled LEDs with CCT of 3000 K and a CRI 90; the source luminous flux is 8741 lm, with a 102.8 lm/W nominal luminous efficacy.

The device body is made of aluminium and features a embossed black ral 9005 finish, processed by means of coating; the diffuser is made of PC; the mounting frame is made of metal, with a embossed black ral 9005 finish, processed by means of coating. The ingress protection degree is IP20; the total weight is of 6.3 kg.

The total absorbed power is 89 W. The power supply cable is included and features a 5000 m lenght.

The device features protection class I and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.



Classe d'efficacité énergétique
Ce produit contient 6 sources lumineuses de classe d'efficacité énergétique F.

Caractéristiques Techniques de l'éclairage	
Light Output Ratio (LOR)	81 %
Flux lumineux (source)	8741 lm
Flux lumineux du luminaire	7091 lm
Consumption	89 W
Efficacité lumineuse du luminaire	79 lm/W
Température de couleur	3000 K
Standards de Concordance de Couleur	3 Step MacAdam
Indice de rendu chromatique	90 Ra
Température de jonction (appareil)	80
Température standard de l'environnement de	25°C

LED Life / Failure Ratio
L70 B20 C0 72500h (at Tj 115 Ta 25)

OPTICAL	
Light distribution simmetry	Symmetrical 2 assis
Optique C0/C180	139°
Optique C90/C270	99°

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.

Quad_P9 | Pendant Luminaires | Accessories
8523



Variateur
Bluetooth, 220-240V

Code
KIT0079

Linea Light Group reserves the right, without any advance notice, to change the characteristics of their products, as well as the availability of the same at any time. No product, relative technical data, illustrations and information are binding for Linea Light Group. Linea Light Group will not be held liable for any illustration, text and/or translation\ errors. All values indicated are measured values. There is a +/- 10% tolerance for the flow, CCT and power data.