


Periscopio



Table Lamps | 220-240 V | 1xG9
9056



| Technical data | |
|--|----------|
| Installation position | Floor |
| Installation environment | Indoor |
| Lamp cap | 1 x G9 |
| Frequency | 50-60 Hz |
| Optics | Diffused |
| Safety class | 2 |
| IP | IP20 |
| Glow wire test | 650° |
| Direct mounting on normally flammable surfaces | Yes |
| CE | Yes |
| Dimmable article | No |
| Directional | No |
| Tilting | Yes |
| total angle (horizontal plane) | 330 ° |
| total angle (vertical plane) | 180 ° |
| Walk-over | No |
| Drive-over | No |
| Cable included | Yes |
| Electric socket | Type C |
| Cable length | 2 m |
| Resin potting | No |
| Net weight | 4,295 Kg |

| Finishing casing | |
|------------------|----------------|
| Material | AISI 304 steel |
| Processing | Coating |

| Finishing diffuser | |
|--------------------|---------------------------|
| Material | Glass - Glass |
| Colour | white - grey |
| Processing | Satin finishing - Coating |

| Finishing base | |
|----------------|---------|
| Material | Iron |
| Processing | Coating |



Table Lamps | 220-240 V | 1xG9
9056

Double emission table lamps for indoor application. LED lamplamp included, lamp cap 1xG9.

The device body is made of aisi 304 steel, processed by means of coating; the diffuser is made of glass with a satin finishing treatment; the diffuser is made of glass with a coating treatment. The ingress protection degree is IP20; the total weight is of 4,295 kg.

. The power supply cable is included and features a 2 m length.

The device features protection class II and can be floor-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Energy efficiency class

This product contains a light source of energy efficiency class F.

Illuminotechnical Features

| | |
|---------------|--------|
| Source lumens | 700 lm |
|---------------|--------|

| | |
|--------------------|--------|
| Colour temperature | 3000 K |
|--------------------|--------|

| | |
|------------------------|-------|
| Colour rendering index | 80 Ra |
|------------------------|-------|

| | |
|---|----|
| Junction temperature (lighting fixture) | 80 |
|---|----|

| | |
|--|------|
| Standard Operating Ambient Temperature | 25°C |
|--|------|